



HYCD-319A

Combined Refrigerator and Freezer

Scope of Application

This product is designed to store frozen plasma, biomaterials, vaccines, electronic devices and low temperature tests of special materials, in blood stations, hospitals, epidemic prevention stations, universities, scientific research institutes, electronic chemical industry and other enterprise laboratories.

Innovative Design

- Intelligent Microprocessor with Digital Display
- Natural Hydrocarbon Refrigerant
- Stainless Steel Interior
- Audible and Visual Alert with Remote Alarm Contact
- Self-closing Door with Magnetic Gasket
- Padlock to Secure Safe Storage

Qingdao Haier Biomedical Co.,Ltd.

No.280 Feng Yuan Road, High-tech Zone,
Qingdao, 266109, P.R. China
E-mail: inquiry@haierbiomedical.com
Website: www.haiermedical.com



Haier Biomedical
International



Haier Biomedical
International



@haiermedicalint



Haier Biomedical
International



Haier Biomedical
International

Product Advantages



Multipurpose and Space Efficient

- One cabinet with two independent chambers, both are self-contained and independently controlled with individual doors
- Refrigerator chamber is equipped with a double-paned glass viewing window and LED interior lighting



Environment Friendly

Hydrocarbon refrigerant (R600a for refrigerator / R290 for freezer) and CFC-free polyurethane insulation for reduced global warming potential



Stainless Steel Interior

The interior of refrigerator and freezer are both made of stainless steel, which is easy to clean and corrosion-proof



Microprocessor Controller with Digital Display

- Refrigerator temperature 2-8°C with resolution of 0.1°C
- Freezer temperature -40~-10°C with resolution of 1°C
- Multiple alarm functions with remote alarm contact to ensure safe monitoring



High Performance

- Refrigerator: Forced-air cooling system with cycle defrost, temperature uniformity $\pm 3^{\circ}\text{C}$
- Freezer: Cold wall cooling system, manual defrost, temperature uniformity $\pm 5^{\circ}\text{C}$
- Standard USB port & optional printer, easy to get temperature record

Ergonomic Design



Equipped with padlocks in both refrigerator and freezer to ensure storage safety



Equipped with electrically heated glass to prevent condensation effectively




Two test holes for both refrigerator and freezer as standard, allow independent testing of cabinet temperature



Refrigerator and freezer are equipped with self-closing hinges to avoid door ajar (less than 90° self-closing)


Product Parts




Product Performance




Refrigerator Cool Down Curve




Freezer Cool Down Curve




Refrigerator Stability Curve



Freezer Stability Curve



Dimensions



Specifications



Model			HYCD-319A	
Technical Data	Cabinet Type		Refrigerator	Freezer
			Upright	
	Climate Class		N	
	Cooling Type		Forced Air Cooling	Direct Cooling
	Defrost Mode		Auto	Manual
	Refrigerant		HC	HC
	Sound Level (dB(A))		50	
Performance	Temperature Range (°C)		2~8	-15~-40
Control	Controller		Microprocessor	
	Display		LED	
Electrical Data	Power Supply (V/Hz)		115/60	
	Power (W)		450	
	Electrical Current (A)		6	
Dimensions	Capacity (L/Cu.Ft)		200/7.06	100/3.53
	Net/Gross Weight (approx)	kg	145/160	
		lbs	319.7/352.7	
	Interior Dimensions (W*D*H)	mm	605*510*720	515*465*440
		in	23.8*20*28.3	20.2*18.3*17.3
	Exterior Dimensions (W*D*H)	mm	735*660*1810	
		in	28.9*26.0*71.3	
	Packing Dimensions (W*D*H)	mm	795*740*2010	
		in	31.3*29.1*79.1	
	Container Load (20'/40'/40'H)		21/43/43	
Alarms	High/Low Temperature		Y	
	Sensor Error		Y	
	Power Failure		Y	
	Door Ajar		Y	
	High Ambient Temp		Y	
	Low Battery		Y	
	Remote Alarm		Y	
Accessories	Caster		Y/4	
	Foot		Y/2	
	Porthole		Y/2	
	Shelves/Drawers		3/1	1 (For supporting the upper drawer) / 2 (without sliding rack)
	Stylus printer/RS485		Optional (printer or RS 485, either-or)	
	USB Interface		Y	
Others	Certification		UL	

Product appearance and specifications are subject to change without notice